

Style UL10491 Hook-up Wire

Internal wiring of Appliances; or where exposed to oil at a temperature not exceeding 105°C
Whichever is applicable, The most popular hookup wire for Electric.

Description:

Rated temperature: 105°C , Voltage 300V
Conductor:The tinned or bare stranded copper
Insulation: FEP, ETFE or PFA
Shield:The tinned copper braided or wrap
Jacket: PTFE, FEP, PFA
RoHS Compliant



Specification:

Conductor			Insulation		Shield thickness mm	Jacket thickness		Overall Dia.		Max. Resistance	Package
Gauge AWG	NO. / mm	Dia. mm	Avg. Thick. mm	Min. Dia. mm		Avg. mm	Min. mm	Avg. mm	Min. mm	At 20°C Ohm/km	Ft/ roll
20	21/0.18	0.92	0.23	0.18	0.15	0.38	0.33	2.55	2.47	36.7	2000
22	17/0.16	0.76	0.23	0.18	0.15	0.38	0.33	2.36	2.28	59.4	2000
24	11/0.16	0.61	0.23	0.18	0.15	0.38	0.33	2.21	2.13	94.2	2000
26	7/0.16	0.48	0.23	0.18	0.15	0.38	0.33	2.08	2.00	150	2000

Order reference:

- 1.Marking and shield-percent <Optional>
2. Single wire conductor tolerance: +/-0.005mm
3. Colors available: black,white,red,yellow,green,blue,brown,gray,violet
4. Delivery : 7 days after accepting purchase orders.