

Style UL10507 Hook-up Wire

Internal wiring of Appliances; or where exposed to oil at a temperature not exceeding 105°C
Whichever is applicable, The most popular hookup wire for Electric.

Description:

Rated temperature 105°C, Voltage 30V
Conductor:The tinned or bare stranded copper
Insulation: PFA, FEP, PTFE, ETFE or XLPE
Shield:The tinned copper braided or wrap
Jacket: ETFE or PVC
RoHS Compliant



Specification:

Conductor			Insulation		Shield thickness mm	Jacket thickness		Overall Dia.		Max. Resistance	Package
Gauge AWG	NO. / mm	Dia. mm	Avg. Thick. mm	Min. Dia. mm		Avg. mm	Min. mm	Avg. mm	Min. mm	At 20°C Ohm/km	Ft/ roll
20	19/0.19	0.95	0.23	0.18	0.15	0.38	0.33	2.55	2.47	36.7	2000
22	19/0.15	0.75	0.23	0.18	0.15	0.38	0.33	2.35	2.27	59.4	2000
24	7/0.20	0.61	0.23	0.18	0.15	0.38	0.33	2.21	2.13	94.2	2000
26	7/0.16	0.48	0.23	0.18	0.15	0.38	0.33	2.08	2.00	150	2000

Order reference:

- 1.Marking and shield-percent <Optional>
2. Single wire conductor tolerance: +/-0.005mm
3. Colors available: black,white,red,yellow,green,blue,brown,gray,violet
4. Delivery : 7 days after accepting purchase orders.