

Silicone /Glass Braid Insulated material

Style UL3207 Hook-up Wire

Internal wiring of appliances or electric clothes, dryers where exposed to temperature not exceeding 150 °C.

Description:

Conductor material of Tinned or bare copper

Rated temperature 150 °C

Rated Voltage 600 V (Spark voltage 6000 V)

Flame resistance FT2

RoHS Compliant

Covering for fiberglass braid

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
18	1	18	.0402	1.02	.1780	4.52	6.77	22.2	18.91	28.13
18	7	26	.0465	1.18	.1843	4.68	7.06	23.2	19.83	29.50
18	16	30	.0465	1.18	.1843	4.68	7.06	23.2	19.67	29.27
18	19	31	.0465	1.18	.1843	4.68	7.06	23.2	19.75	29.39
18	41	34	.0465	1.18	.1843	4.68	7.06	23.2	19.76	29.39

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Stripping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available