

PVC Insulated material

Style UL20482 Hook-up Wire

Internal wiring of Appliances; or where exposed to oil at a temperature not exceeding 60°C
Whichever is applicable, The most popular hookup wire for Electric.

Description:

Rated temperature 60°C, Voltage 30V


Conductor: The tinned or bare stranded copper

Insulation: PVC

Shield: The tinned copper braided or wrap

Jacket: PVC

RoHS Compliant



Specification:

Conductor				Insulation		Shield thickness mm	Jacket thickness		Overall Dia.		Max. Resistance	Pack- age
Cores No.	Gauge AWG	NO. / mm	Dia. mm	Nom. Thick. mm	Nom. Dia. mm		AVG. mm	Min. mm	AVG. mm	Min. mm	At 20°C Ohm/km	Ft/roll
2	26	7/0.16	0.48	0.25	0.98	0.20	0.38	0.33	3.12	2.82	150	1000
2	24	11/0.16	0.61	0.25	1.11	0.20	0.38	0.33	3.38	3.08	94.2	1000
2	22	17/0.16	0.76	0.25	1.26	0.20	0.38	0.33	3.67	3.37	59.4	1000
2	20	26/0.16	0.95	0.25	1.45	0.20	0.38	0.33	4.06	3.76	36.7	1000
3	26	7/0.16	0.48	0.25	0.98	0.20	0.38	0.33	3.12	2.82	150	1000
3	24	11/0.16	0.61	0.25	1.11	0.20	0.38	0.33	3.38	3.08	94.2	1000
3	22	17/0.16	0.76	0.25	1.26	0.20	0.38	0.33	3.67	3.37	59.4	1000
3	20	26/0.16	0.95	0.25	1.45	0.20	0.38	0.33	4.06	3.76	36.7	1000
4	28	7/0.127	0.38	0.25	0.88	0.20	0.38	0.33	3.19	2.89	239	1000
4	26	7/0.16	0.48	0.25	0.98	0.20	0.38	0.33	3.42	3.12	150	1000
5	28	7/0.127	0.38	0.25	0.88	0.20	0.38	0.33	3.43	3.13	239	1000
5	26	7/0.16	0.48	0.25	0.98	0.20	0.38	0.33	3.69	3.39	150	1000
6	28	7/0.127	0.38	0.25	0.88	0.20	0.38	0.33	3.65	3.35	239	1000
6	26	7/0.16	0.48	0.25	0.98	0.20	0.38	0.33	3.93	3.63	150	1000
7	28	7/0.127	0.38	0.25	0.88	0.20	0.38	0.33	3.86	3.56	239	1000
7	26	7/0.16	0.48	0.25	0.98	0.20	0.38	0.33	4.15	3.85	150	1000

Order reference:

1. Marking and shield-percent <Optional>
2. Single wire conductor tolerance: ± 0.005 mm
3. Colors available: black, white, red, yellow, green, blue, brown, gray, violet
4. Delivery : 7 days after accepting purchase orders.