

PVC Insulated material

Style UL1211 Hook-up Wire

Internal wiring of Appliances; or where exposed to oil at a temperature not exceeding 60 °C
Whichever is applicable, The most popular hookup wire for Electric.

Description:

Conductor material of tinned or bare copper

Rated temperature 60 °C

Rated Voltage 300 V (Spark voltage 3000 V)

Flame resistance VW-1 and FT1

RoHS Compliant

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./ 1000 ft.	Kg/Km
24	1	24	.0201	0.51	.0516	1.31	27.3	89.3	2.36	3.52
24	7	32	.0240	0.61	.0555	1.41	28.7	94.2	2.58	3.84
24	11	34	.0240	0.61	.0555	1.41	28.7	94.2	2.61	3.85
26	1	26	.0157	0.40	.0472	1.20	43.5	143	1.75	2.61
26	7	34	.0197	0.50	.0512	1.30	45.8	150	1.97	2.93
28	1	28	.0126	0.32	.0441	1.12	69.3	227	1.38	2.05
28	7	36	.0154	0.39	.0469	1.19	72.8	239	1.53	2.26

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available