

Silicone /Glass Braid Insulated material

Style UL3125 Hook-up Wire

Internal wiring of appliances or electric clothes, dryers where exposed to temperature not exceeding 200 °C

Description:

Conductor material of Tinned, Nickel or Silvered copper

"*" Conductor material used only Nickel or Silvered copper per ASTM B3/33

Rated temperature 200 °C

Rated Voltage 600 V (Spark voltage 6000 V)

Flame resistance FT2

RoHS Compliant

Covering for fiberglass braid

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
2	259	26	.2854	7.25	.4169	10.59	0.1641	0.5384	229.98	342.17
4	133	25	.2386	6.06	.3701	9.40	0.2608	0.8559	167.94	249.86
6	266	30	.1882	4.78	.3197	8.12	0.4148	1.361	112.52	167.41
8	168	30	.1496	3.80	.2811	7.14	0.6795	2.230	77.79	115.73

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available