

XLPE Insulated material

Style UL3599 Hook-up Wire

Internal wiring of electronic equipment.

Description:

Conductor material of Tinned or Bare copper

Rated temperature 80°C

Rated Voltage 300 V (Spark voltage 3000 V)

Flame resistance FT2

RoHS Compliant

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
10	105	30	.1181	3.00	.1417	3.60	1.08	3.55	35.24	52.43
12	65	30	.0933	2.37	.1169	2.97	1.72	5.64	22.40	33.32
14	41	30	.0740	1.88	.0976	2.48	2.73	8.96	14.59	21.71
16	7	25	.0591	1.50	.0787	2.00	4.45	14.6	9.48	14.10
16	19	29	.0591	1.50	.0787	2.00	4.45	14.6	9.48	14.10
16	26	30	.0591	1.50	.0787	2.00	4.45	14.6	9.32	13.87
18	1	18	.0402	1.02	.0598	1.52	6.77	22.2	5.93	8.82
18	16	30	.0465	1.18	.0661	1.68	7.06	23.2	6.01	8.94
18	7	26	.0465	1.18	.0661	1.68	7.06	23.2	6.16	9.17
18	19	31	.0465	1.18	.0661	1.68	7.06	23.2	6.09	9.06
20	1	20	.0320	0.813	.0517	1.31	10.7	35.2	3.96	5.90
20	10	30	.0374	0.95	.0571	1.45	11.2	36.7	4.14	6.16
20	19	33	.0374	0.95	.0571	1.45	11.2	36.7	4.19	6.23
20	21	33	.0374	0.95	.0571	1.45	11.2	36.7	4.16	6.19
22	7	30	.0299	0.76	.0496	1.26	18.1	59.4	2.85	4.24
22	17	34	.0299	0.76	.0496	1.26	18.1	59.4	2.85	4.24
24	11	34	.0240	0.61	.0437	1.11	28.7	94.2	2.00	2.98
26	7	34	.0197	0.50	.0394	1.00	45.8	150	1.43	2.13
28	7	36	.0154	0.39	.0350	0.89	72.8	239	1.03	1.54
30	1	30	.0100	0.254	.0297	0.75	110	361	0.70	1.04

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Stripping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available